

Technical Specifications OABC D (18-55 kW)

MODEL	Motor Power		Inlet (FAD)		Outlet (FAD)				Dimensions (inch)		
	kW	hp	PSI	Bar	PSI	Bar	cfm	m ³ /min	W	L	H
OABC D 18	18,5	25	102	7	580	40	74,2	2,1	54,9	82,5	61,0
			145	10			116,5	3,3			
OABC D 22	22	30	102	7	580	40	84,8	2,4	54,9	82,5	61,0
			145	10			155,4	4,4			
OABC D 30	30	40	102	7	580	40	120,1	3,4	54,9	82,5	61,0
			145	10			202,9	5,7			
OABC D 37	37	50	102	7	580	40	158,9	4,5	54,9	82,5	61,0
			145	10			336,7	9,5			
OABC D 45	45	60	102	7	580	40	208,4	5,9	54,9	82,5	61,0
			189	13			427,3	12,1			
OABC D 55	55	75	102	7	580	40	293,1	8,3	58,9	86,4	61,0
			189	13			452,0	12,8			

Compressor performance measured according to ISO 1217, Annex C Edt. 4 (2009).

Reference conditions:

- Absolute inlet pressure 14,5 psi (1 bar)
- Intake air temperature 68°F (20°C)